



# AXRO IN-2

ELASTIC BINDER

**CYKLOP**<sup>®</sup>  
GLOBAL PACKAGING SOLUTIONS

STRAPPING  
WRAPPING  
CODING  
TAPING

The AXRO IN-2 is specially developed to bind ring shaped products with a minimum inner core diameter of 35 mm. The AXRO IN-2 is provided with the well-known AXRO gripping and knotting technology, which has been successfully used for many years in the other AXRO models. This machine is suited for bundling cables, cords and other rolled up products.

**Advantages**

- For elastic cord Cylastic PES, Cylastic PCs 1300, Cylastic 3K
- Bundles inner core diameter of just 35 mm
- Extremely easy operation
- Robust, hard-wearing, very reliable
- Minimal maintenance
- Automatic and fully automatic available
- Up to 75 cycles / minute
- Can be integrated into automatic machine lines

**Options:**

- Undercarriage
- I/O connector for signal exchange
- Elastic cord detection
- Nearly empty spool detection
- Needle in home position detection (ready for next cycle)
- Starter switch in tabletop



[< CLICK HERE FOR A VIDEO OF THE AXRO IN-2 >](#)



Technical data	
Capacity	Up to 75 cycles/minute
Dimensions (HxWxD)	1020 x 557 x 402 mm
Transit depth	150 x 250 mm
	Minimal inside diameter 35 mm
Input	Left (standard), right optional
Tabletop	RVS
Start switch	Foot pedal
String tension	Adjustable up to 110 N
Consumables	Cylastic PES, Pcs 1300, 3K
Power supply	200-240 V, 50/60 Hz, 1 Phase
	100-120 V, 50/60 Hz, 1 Phase
Weight	75 kg